

MARELUCE
decorative

pales-1



Technical Data	
Power	6W
Voltage Supply	3-45VDC (Driver Ext.)
Dimmable	Yes / PWM
Color Temp.	2700K-3000K-4000K
Luminous Flux	110lm/Watt (Max.)
Light Source	COB Led / CRI>80
Beam	15°-30°-60°
Body Material	SS 316L
Body Finishes	PSS-S5S-G-MBR-RAL
IP Class	44

Dimensions



Model	a	b	c
Pales-1	100mm	80mm	45mm

Options Controls



pales-2



Technical Data	
Power	6Wx2
Voltage Supply	3-45VDC (Driver Ext.)
Dimmable	Yes / PWM
Color Temp.	2700K-3000K-4000K
Luminous Flux	110lm/Watt (Max.)
Light Source	COB Led / CRI>80
Beam	15°-30°-60°
Body Material	SS 316L
Body Finishes	PSS-S5S-G-MBR-RAL
IP Class	44

Dimensions



Model	a	b	c
Pales-2	175mm	155mm	45mm

Options Controls



pales-3



Technical Data	
Power	6Wx3
Voltage Supply	3-45VDC (Driver Ext.)
Dimmable	Yes / PWM
Color Temp.	2700K-3000K-4000K
Luminous Flux	110lm/Watt (Max.)
Light Source	COB Led / CRI>80
Beam	15°-30°-60°
Body Material	SS 316L
Body Finishes	PSS-S5S-G-MBR-RAL
IP Class	44

Dimensions



Model	a	b	c
Pales-3	250mm	230mm	45mm

Options Controls




penates-1



Technical Data	
Power	6W
Voltage Supply	3-45VDC (Driver Ext.)
Dimmable	Yes / PWM
Color Temp.	2700K-3000K-4000K
Luminous Flux	110lm/Watt (Max.)
Light Source	COB Led / CRI>80
Beam	15°-30°-60°
Body Material	SS 316L
Body Finishes	PSS-S5S-G-MBR-RAL
IP Class	44

Dimensions



Model	a	b
Penates-1	77mm	77mm

Options Controls



penates-2



Technical Data	
Power	6Wx2
Voltage Supply	3-45VDC (Driver Ext.)
Dimmable	Yes / PWM
Color Temp.	2700K-3000K-4000K
Luminous Flux	110lm/Watt (Max.)
Light Source	COB Led / CRI>80
Beam	15°-30°-60°
Body Material	SS 316L
Body Finishes	PSS-S5S-G-MBR-RAL
IP Class	44

Dimensions



Model	a	b
Penates-2	152mm	77mm

Options Controls



penates-3



Technical Data	
Power	6Wx3
Voltage Supply	3-45VDC (Driver Ext.)
Dimmable	Yes / PWM
Color Temp.	2700K-3000K-4000K
Luminous Flux	110lm/Watt (Max.)
Light Source	COB Led / CRI>80
Beam	15°-30°-60°
Body Material	SS 316L
Body Finishes	PSS-S5S-G-MBR-RAL
IP Class	44

Dimensions



Model	a	b
Penates-3	227mm	77mm

Options Controls




nox-3



Technical Data	
Power	3W
Voltage Supply	10-32VDC (Driver Ext.)
Dimmable	Yes / PWM
Color Temp.	2700K-3000K-4000K
Luminous Flux	125lm/Watt (Max.)
Light Source	High Power Led / CRI>80
Beam	Middle
Body Material	Aluminum
Body Finishes	RAL
IP Class	44

Dimensions



Model	a	b	c
Nox-3	45mm	35mm	45mm

Options Controls




nox-4



Technical Data	
Power	6W
Voltage Supply	12-32VDC (Driver Ext.)
Dimmable	Yes / PWM
Color Temp.	2700K-3000K-4000K
Luminous Flux	125lm/Watt (Max.)
Light Source	High Power Led / CRI>80
Beam	Middle
Body Material	Aluminum
Body Finishes	RAL
IP Class	44

Dimensions



Model	a	b	c
Nox-4	45mm	35mm	45mm

Options Controls



nox-5



Technical Data	
Power	12W
Voltage Supply	18-32VDC (Driver Ext.)
Dimmable	Yes / PWM
Color Temp.	2700K-3000K-4000K
Luminous Flux	125lm/Watt (Max.)
Light Source	High Power Led / CRI>80
Beam	Middle
Body Material	Aluminum
Body Finishes	RAL
IP Class	44

Dimensions



Model	a	b	c
Nox-5	45mm	35mm	45mm

Options Controls




nox-f3



Technical Data	
Power	3W
Voltage Supply	10-32VDC (Driver Ext.)
Dimmable	Yes / PWM
Color Temp.	2700K-3000K-4000K
Luminous Flux	125lm/Watt (Max.)
Light Source	High Power Led / CRI>80
Beam	Middle
Body Material	Aluminum
Body Finishes	RAL
IP Class	44

Dimensions



Model	a	b	c
Nox-f3	37mm	97mm	45mm

Options Controls




nox-f4



Technical Data	
Power	6W
Voltage Supply	12-32VDC (Driver Ext.)
Dimmable	Yes / PWM
Color Temp.	2700K-3000K-4000K
Luminous Flux	125lm/Watt (Max.)
Light Source	High Power Led / CRI>80
Beam	Middle
Body Material	Aluminum
Body Finishes	RAL
IP Class	44

Dimensions



Model	a	b	c
Nox-f4	37mm	117mm	45mm

Options Controls




nox-f5



Technical Data	
Power	12W
Voltage Supply	18-32VDC (Driver Ext.)
Dimmable	Yes / PWM
Color Temp.	2700K-3000K-4000K
Luminous Flux	125lm/Watt (Max.)
Light Source	High Power Led / CRI>80
Beam	Middle
Body Material	Aluminum
Body Finishes	RAL
IP Class	44

Dimensions



Model	a	b	c
Nox-f5	37mm	137mm	45mm

Options Controls




seginus



Technical Data	
Power	3W-6W-12W (3 Model)
Voltage Supply	8-32VDC (Driver Inc.)
Dimmable	Yes / PWM
Color Temp.	2700K-3000K-4000K-DW-RGB
Luminous Flux	125lm/Watt (Max.)
Light Source	High Power Led / CRI>80
Beam	Wide
Body Material	SS 316L - Aluminum
Body Finishes	PSS-SSS-G-MBR-RAL
IP Class	44 - 66

Dimensions



Model	a	b
Seginus-60	60mm	25mm
Seginus-90	90mm	35mm
Seginus-110	110mm	45mm

Options Controls




venus



Technical Data	
Power	3W-6W-12W (3 Model)
Voltage Supply	8-32VDC (Driver Inc.)
Dimmable	Yes / PWM
Color Temp.	2700K-3000K-4000K-DW-RGB
Luminous Flux	125lm/Watt (Max.)
Light Source	High Power Led / CRI>80
Beam	Wide
Body Material	SS 316L - Aluminum
Body Finishes	PSS-SSS-G-MBR-RAL
IP Class	44 - 66

Dimensions



Model	a	b
Venus-60	60mm	25mm
Venus-90	90mm	35mm
Venus-110	110mm	45mm

Options Controls




rumina



Technical Data	
Power	3W-6W-12W (3 Model)
Voltage Supply	8-32VDC (Driver Inc.)
Dimmable	Yes / PWM
Color Temp.	2700K-3000K-4000K
Luminous Flux	125lm/Watt (Max.)
Light Source	High Power Led / CRI>80
Beam	Middle
Body Material	SS 316L - Aluminum
Body Finishes	PSS-SSS-G-MBR-RAL
IP Class	44 - 66

Dimensions



Model	a	b
Rumina-40	40mm	60mm
Rumina-60	60mm	80mm
Rumina-80	80mm	100mm

Options Controls




alfa-1



Technical Data	
Power	6W
Voltage Supply	18-32VDC (Driver Ext.)
Dimmable	Yes / PWM
Color Temp.	2700K-3000K-4000K
Luminous Flux	125lm/Watt (Max.)
Light Source	High Power Led / CRI>80
Beam	130°
Body Material	SS 316L - Aluminum
Body Finishes	PSS-SSS-G-MBR-RAL
IP Class	44-66

Dimensions



Model	a	b
Alfa-1	100mm	85mm

Options Controls




alfa-2



Technical Data	
Power	12W
Voltage Supply	18-32VDC (Driver Ext.)
Dimmable	Yes / PWM
Color Temp.	2700K-3000K-4000K
Luminous Flux	125lm/Watt (Max.)
Light Source	High Power Led / CRI>80
Beam	130°
Body Material	SS 316L - Aluminum
Body Finishes	PSS-SSS-G-MBR-RAL
IP Class	44-66

Dimensions



Model	a	b
Alfa-2	100mm	100mm

Options Controls




astra



Technical Data	
Power	4W-8W-12W (3 Model)
Voltage Supply	3-45VDC (Driver Inc.)
Dimmable	Yes / PWM
Color Temp.	2700K-3000K-4000K-6500K
Luminous Flux	110lm/Watt (Max.)
Light Source	COB Led / CRI>90
Beam	45°
Body Material	SS 316L - Aluminum
Body Finishes	PSS-SSS-G-MBR-RAL
IP Class	66

Dimensions



Model	a	b
Astra-50	50mm	100mm
Astra-70	70mm	100mm
Astra-90	90mm	120mm

Options Controls




mena-17



Technical Data

Power	15W / mt.
Voltage Supply	12VDC - 24VDC
Dimmable	Yes / PWM
Color Temp.	2700K-3000K-4000K-DW
Luminous Flux	125lm/Watt (Max.)
Light Source	Mid. Power Led / CRI>90
Beam	Wide
Body Material	Aluminum
Body Finishes	RAL
IP Class	44 - 66

Dimensions



Model	a	b	c
Mena-17	38mm	20mm	40mm

Options Controls




mena-35



Technical Data

Power	25W / mt.
Voltage Supply	12VDC - 24VDC
Dimmable	Yes / PWM
Color Temp.	2700K-3000K-4000K-DW
Luminous Flux	125lm/Watt (Max.)
Light Source	Mid. Power Led / CRI>90
Beam	Wide
Body Material	Aluminum
Body Finishes	RAL
IP Class	44 - 66

Dimensions



Model	a	b	c
Mena-35	50mm	35mm	45mm

Options Controls




mena-50



Technical Data

Power	42W / mt.
Voltage Supply	12VDC - 24VDC
Dimmable	Yes / PWM
Color Temp.	2700K-3000K-4000K-DW
Luminous Flux	125lm/Watt (Max.)
Light Source	Mid. Power Led / CRI>90
Beam	Wide
Body Material	Aluminum
Body Finishes	RAL
IP Class	44 - 66

Dimensions



Model	a	b	c
Mena-50	75mm	50mm	55mm

Options Controls



nena-35



Technical Data

Power	20W / mt.
Voltage Supply	12VDC - 24VDC
Dimmable	Yes / PWM
Color Temp.	2700K-3000K-4000K-DW
Luminous Flux	125lm/Watt (Max.)
Light Source	Mid. Power Led / CRI>90
Beam	Wide
Body Material	Aluminum
Body Finishes	RAL
IP Class	44 - 66

Dimensions



Model	a	b
Nena-35	35mm	70mm

Options Controls

