

MARELUCE
downlight

vesta



Technical Data	
Power	3W-6W-12W (3 Model)
Voltage Supply	8-32VDC (Driver Inc.)
Dimmable	Yes / PWM
Color Temp.	2700K-3000K-4000K-DW
Luminous Flux	125lm/Watt (Max.)
Light Source	High Power Led / CRI>80
Beam	Middle
Body Material	SS 316L - Aluminum
Body Finishes	PSS-SSS-G-MBR-RAL
IP Class	44 - 66

Dimensions			
	a	b	c
Vesta-40	50mm	40mm	45mm
Vesta-55	70mm	55mm	45mm
Vesta-70	85mm	70mm	45mm



vesta-da



Technical Data	
Power	3W-6W-12W (3 Model)
Voltage Supply	8-32VDC (Driver Inc.)
Dimmable	Yes / PWM
Color Temp.	2700K-3000K-4000K-DW
Luminous Flux	125lm/Watt (Max.)
Light Source	High Power Led / CRI>80
Beam	Middle
Body Material	SS 316L - Aluminum
Body Finishes	PSS-SSS-G-MBR-RAL
IP Class	44 - 66

Dimensions			
	a	b	c
Vesta-da-40	50mm	40mm	65mm
Vesta-da-55	70mm	55mm	65mm
Vesta-da-70	85mm	70mm	65mm



sors



Technical Data	
Power	5W-8W-12W (3 Model)
Voltage Supply	3-45VDC (Driver Ext.)
Dimmable	Yes / PWM
Color Temp.	2700K-3000K-4000K
Luminous Flux	110lm/Watt (Max.)
Light Source	COB Led / CRI>80
Beam	15°-30°-60°
Body Material	SS 316L - Aluminum
Body Finishes	PSS-SSS-G-MBR-RAL
IP Class	44 - 66

Dimensions			
	a	b	c
Sors-40	60mm	40mm	45mm
Sors-55	75mm	55mm	45mm
Sors-70	90mm	70mm	45mm



sors-a



Technical Data	
Power	3W-6W-12W (3 Model)
Voltage Supply	8-32VDC (Driver Inc.)
Dimmable	Yes / PWM
Color Temp.	2700K-3000K-4000K-DW
Luminous Flux	125lm/Watt (Max.)
Light Source	High Power Led / CRI>80
Beam	Wide
Body Material	SS 316L - Aluminum
Body Finishes	PSS-SSS-G-MBR-RAL
IP Class	44 - 66

Dimensions			
	a	b	c
Sors-a-40	60mm	40mm	65mm
Sors-a-55	75mm	55mm	65mm
Sors-a-70	90mm	70mm	65mm



sors-da



Technical Data	
Power	3W-6W-12W (3 Model)
Voltage Supply	8-32VDC (Driver Inc.)
Dimmable	Yes / PWM
Color Temp.	2700K-3000K-4000K-DW
Luminous Flux	125lm/Watt (Max.)
Light Source	High Power Led / CRI>80
Beam	Wide
Body Material	SS 316L
Body Finishes	PSS-SSS-G-MBR-RAL
IP Class	44 - 66

Dimensions			
	a	b	c
Sors-da-40	60mm	40mm	45mm
Sors-da-55	75mm	55mm	45mm
Sors-da-70	90mm	70mm	45mm



ceres



Technical Data	
Power	3W-6W-12W (3 Model)
Voltage Supply	3-45VDC (Driver Ext.)
Dimmable	Yes / PWM
Color Temp.	2700K-3000K-4000K
Luminous Flux	110lm/Watt (Max.)
Light Source	COB Led / CRI>90
Beam	15°-30°-60°
Body Material	SS 316L
Body Finishes	PSS-SSS-G-MBR-RAL
IP Class	44 - 66

Dimensions			
	a	b	c
Ceres-40	55mm	40mm	45mm
Ceres-60	75mm	60mm	50mm
Ceres-80	95mm	80mm	65mm



ceres-a



Technical Data	
Power	3W-6W-12W (3 Model)
Voltage Supply	3-45VDC (Driver Inc.)
Dimmable	Yes / PWM
Color Temp.	2700K-3000K-4000K
Luminous Flux	110lm/Watt (Max.)
Light Source	COB Led / CRI>90
Beam	15°-30°-60°
Body Material	SS 316L
Body Finishes	PSS-SSS-G-MBR-RAL
IP Class	44 - 66

Dimensions			
	a	b	c
Ceres-a-40	55mm	40mm	45mm
Ceres-a-60	75mm	60mm	50mm
Ceres-a-80	95mm	80mm	65mm



flora



Technical Data	
Power	3W-6W-12W (3 Model)
Voltage Supply	3-45VDC (Driver Inc.)
Dimmable	Yes / PWM
Color Temp.	2700K-3000K-4000K
Luminous Flux	110lm/Watt (Max.)
Light Source	COB Led / CRI>90
Beam	15°-30°-60°
Body Material	SS 316L
Body Finishes	PSS-SSS-G-MBR-RAL
IP Class	44 - 66

Dimensions			
	a	b	c
Flora-40	55mm	40mm	45mm
Flora-60	75mm	60mm	50mm
Flora-80	95mm	80mm	65mm



flora-a



Technical Data	
Power	3W-6W-12W (3 Model)
Voltage Supply	3-45VDC (Driver Inc.)
Dimmable	Yes / PWM
Color Temp.	2700K-3000K-4000K
Luminous Flux	110lm/Watt (Max.)
Light Source	COB Led / CRI>90
Beam	15°-30°-60°
Body Material	SS 316L
Body Finishes	PSS-SSS-G-MBR-RAL
IP Class	44 - 66

Dimensions			
	a	b	c
Flora-a-40	55mm	40mm	45mm
Flora-a-60	75mm	60mm	50mm
Flora-a-80	95mm	80mm	65mm




orion



Technical Data	
Power	3W-6W-12W (3 Model)
Voltage Supply	8-32VDC (Driver Inc.)
Dimmable	Yes / PWM
Color Temp.	2700K-3000K-4000K-DW+(RED)
Luminous Flux	125lm/Watt (Max.)
Light Source	High Power Led / CRI>80
Beam	Wide
Body Material	SS 316L - Aluminum
Body Finishes	PSS-SSS-G-MBR-RAL
IP Class	44 - 66

Dimensions



Model	a	b	c
Orion-50	65mm	50mm	35mm
Orion-70	85mm	70mm	35mm
Orion-80	95mm	80mm	35mm

Options Controls




orion-a



Technical Data	
Power	3W-6W-12W (3 Model)
Voltage Supply	8-32VDC (Driver Inc.)
Dimmable	Yes / PWM
Color Temp.	2700K-3000K-4000K-DW+(RED)
Luminous Flux	125lm/Watt (Max.)
Light Source	High Power Led / CRI>80
Beam	Wide
Body Material	SS 316L - Aluminum
Body Finishes	PSS-SSS-G-MBR-RAL
IP Class	44 - 66

Dimensions



Model	a	b	c
Orion-a-50	70mm	50mm	35mm
Orion-a-70	90mm	70mm	35mm
Orion-a-80	100mm	80mm	35mm

Options Controls




mars



Technical Data	
Power	3W-6W-12W (3 Model)
Voltage Supply	8-32VDC (Driver Inc.)
Dimmable	Yes / PWM
Color Temp.	2700K-3000K-4000K-DW+(RED)
Luminous Flux	125lm/Watt (Max.)
Light Source	High Power Led / CRI>80
Beam	Wide
Body Material	SS 316L - Aluminum
Body Finishes	PSS-SSS-G-MBR-RAL
IP Class	44 - 66

Dimensions



Model	a	b	c
Mars-50	65mm	50mm	35mm
Mars-70	85mm	70mm	35mm
Mars-80	95mm	80mm	35mm

Options Controls




mars-a



Technical Data	
Power	3W-6W-12W (3 Model)
Voltage Supply	8-32VDC (Driver Inc.)
Dimmable	Yes / PWM
Color Temp.	2700K-3000K-4000K-DW+(RED)
Luminous Flux	125lm/Watt (Max.)
Light Source	High Power Led / CRI>80
Beam	Wide
Body Material	SS 316L - Aluminum
Body Finishes	PSS-SSS-G-MBR-RAL
IP Class	44 - 66

Dimensions



Model	a	b	c
Mars-a-50	70mm	50mm	35mm
Mars-a-70	90mm	70mm	35mm
Mars-a-80	100mm	80mm	35mm

Options Controls




neptune



Technical Data	
Power	3W-6W-12W (3 Model)
Voltage Supply	8-32VDC (Driver Inc.)
Dimmable	Yes / PWM
Color Temp.	2700K-3000K-4000K-DW+(RED)
Luminous Flux	125lm/Watt (Max.)
Light Source	High Power Led / CRI>80
Beam	Wide
Body Material	SS 316L - Aluminum
Body Finishes	PSS-SSS-G-MBR-RAL
IP Class	44 - 66

Dimensions



Model	a	b	c
Neptune-50	65mm	50mm	35mm
Neptune-70	85mm	70mm	35mm
Neptune-80	95mm	80mm	35mm

Options Controls




neptune-a



Technical Data	
Power	3W-6W-12W (3 Model)
Voltage Supply	8-32VDC (Driver Inc.)
Dimmable	Yes / PWM
Color Temp.	2700K-3000K-4000K-DW+(RED)
Luminous Flux	125lm/Watt (Max.)
Light Source	High Power Led / CRI>80
Beam	Wide
Body Material	SS 316L - Aluminum
Body Finishes	PSS-SSS-G-MBR-RAL
IP Class	44 - 66

Dimensions



Model	a	b	c
Neptune-a-50	70mm	50mm	35mm
Neptune-a-70	90mm	70mm	35mm
Neptune-a-80	100mm	80mm	35mm

Options Controls




pluton



Technical Data	
Power	3W-6W-12W (3 Model)
Voltage Supply	8-32VDC (Driver Inc.)
Dimmable	Yes / PWM
Color Temp.	2700K-3000K-4000K-DW+(RED)
Luminous Flux	125lm/Watt (Max.)
Light Source	High Power Led / CRI>80
Beam	Wide
Body Material	SS 316L - Aluminum
Body Finishes	PSS-SSS-G-MBR-RAL
IP Class	44 - 66

Dimensions



Model	a	b	c
Pluton-50	65mm	50mm	35mm
Pluton-70	85mm	70mm	35mm
Pluton-80	95mm	80mm	35mm

Options Controls




pluton-a



Technical Data	
Power	3W-6W-12W (3 Model)
Voltage Supply	8-32VDC (Driver Inc.)
Dimmable	Yes / PWM
Color Temp.	2700K-3000K-4000K-DW+(RED)
Luminous Flux	125lm/Watt (Max.)
Light Source	High Power Led / CRI>80
Beam	Wide
Body Material	SS 316L - Aluminum
Body Finishes	PSS-SSS-G-MBR-RAL
IP Class	44 - 66

Dimensions



Model	a	b	c
Pluton-a-50	70mm	50mm	35mm
Pluton-a-70	90mm	70mm	35mm
Pluton-a-80	100mm	80mm	35mm

Options Controls




jupiter



Technical Data	
Power	3W-6W-12W (3 Model)
Voltage Supply	8-32VDC (Driver Inc.)
Dimmable	Yes / PWM
Color Temp.	2700K-3000K-4000K-DW+(RED)
Luminous Flux	125lm/Watt (Max.)
Light Source	High Power Led / CRI>80
Beam	Wide
Body Material	SS 316L - Aluminum
Body Finishes	PSS-SSS-G-MBR-RAL
IP Class	44 - 66

Dimensions



Model	a	b	c
Jupiter-50	65mm	50mm	35mm
Jupiter-70	85mm	70mm	35mm
Jupiter-80	95mm	80mm	35mm

Options Controls



mercur



Technical Data	
Power	3W-6W-12W (3 Model)
Voltage Supply	8-32VDC (Driver Inc.)
Dimmable	Yes / PWM
Color Temp.	2700K-3000K-4000K-DW+(RED)
Luminous Flux	125lm/Watt (Max.)
Light Source	High Power Led / CRI>80
Beam	Wide
Body Material	SS 316L - Aluminum
Body Finishes	PSS-SSS-G-MBR-RAL
IP Class	44 - 66

Dimensions			
	a	b	c
Merkur-50	65mm	50mm	45mm
Merkur-70	85mm	70mm	50mm
Merkur-80	95mm	80mm	65mm



gloria



Technical Data	
Power	3W-6W-12W (3 Model)
Voltage Supply	8-32VDC (Driver Inc.)
Dimmable	Yes / PWM
Color Temp.	2700K-3000K-4000K-DW+(RED)
Luminous Flux	125lm/Watt (Max.)
Light Source	High Power Led / CRI>80
Beam	Wide
Body Material	SS 316L - Aluminum
Body Finishes	PSS-SSS-G-MBR-RAL
IP Class	44 - 66

Dimensions			
	a	b	c
Gloria-40	55mm	40mm	45mm
Gloria-55	70mm	55mm	50mm
Gloria-70	85mm	70mm	65mm



gloria-a



Technical Data	
Power	3W-6W-12W (3 Model)
Voltage Supply	8-32VDC (Driver Inc.)
Dimmable	Yes / PWM
Color Temp.	2700K-3000K-4000K-DW+(RED)
Luminous Flux	125lm/Watt (Max.)
Light Source	High Power Led / CRI>80
Beam	Wide
Body Material	SS 316L - Aluminum
Body Finishes	PSS-SSS-G-MBR-RAL
IP Class	44 - 66

Dimensions			
	a	b	c
Gloria-a-50	65mm	50mm	45mm
Gloria-a-70	85mm	70mm	50mm
Gloria-a-80	95mm	80mm	65mm



fortuna-ra



Technical Data	
Power	5W-8W-12W (3 Model)
Voltage Supply	3-45VDC (Driver Ext.)
Dimmable	Yes / PWM
Color Temp.	2700K-3000K-4000K
Luminous Flux	110lm/Watt (Max.)
Light Source	COB Led / CRI>80
Beam	15°-30°-60°
Body Material	SS 316L - Aluminum
Body Finishes	PSS-SSS-G-MBR-RAL
IP Class	44 - 66

Dimensions			
	a	b	c
Fortuna-ra-40	55mm	40mm	45mm
Fortuna-ra-55	70mm	55mm	50mm
Fortuna-ra-70	85mm	70mm	65mm



fortuna-sa



Technical Data	
Power	5W-8W-12W (3 Model)
Voltage Supply	3-45VDC (Driver Ext.)
Dimmable	Yes / PWM
Color Temp.	2700K-3000K-4000K
Luminous Flux	110lm/Watt (Max.)
Light Source	COB Led / CRI>80
Beam	15°-30°-60°
Body Material	SS 316L - Aluminum
Body Finishes	PSS-SSS-G-MBR-RAL
IP Class	44 - 66

Dimensions			
	a	b	c
Fortuna-sa-40	55mm	40mm	45mm
Fortuna-sa-55	70mm	55mm	50mm
Fortuna-sa-70	85mm	70mm	65mm



vulcan



Technical Data	
Power	3W-6W-12W (3 Model)
Voltage Supply	8-32VDC (Driver Inc.)
Dimmable	Yes / PWM
Color Temp.	2700K-3000K-4000K-DW+(RED)
Luminous Flux	125lm/Watt (Max.)
Light Source	High Power Led / CRI>80
Beam	Middle
Body Material	SS 316L - Aluminum
Body Finishes	PSS-SSS-G-MBR-RAL
IP Class	44 - 66

Dimensions			
	a	b	c
Vulcan-40	55mm	40mm	45mm
Vulcan-55	70mm	55mm	50mm
Vulcan-70	85mm	70mm	65mm




luna-r



Technical Data	
Power	3W-6W-12W (3 Model)
Voltage Supply	8-32VDC (Driver Inc.)
Dimmable	Yes / PWM
Color Temp.	2700K-3000K-4000K-DW-RGB
Luminous Flux	125lm/Watt (Max.)
Light Source	High Power Led / CRI>80
Beam	Wide
Body Material	Acrylic
Body Finishes	Opal (Clear / Frosted)
IP Class	44 - 66

Dimensions			
	a	b	c
Luna-r-40	55mm	40mm	45mm
Luna-r-55	70mm	55mm	50mm
Luna-r-70	85mm	70mm	65mm



luna-s



Technical Data	
Power	3W-6W-12W (3 Model)
Voltage Supply	8-32VDC (Driver Inc.)
Dimmable	Yes / PWM
Color Temp.	2700K-3000K-4000K-DW-RGB
Luminous Flux	125lm/Watt (Max.)
Light Source	High Power Led / CRI>80
Beam	Wide
Body Material	Acrylic
Body Finishes	Opal (Clear / Frosted)
IP Class	44 - 66

Dimensions			
	a	b	c
Luna-s-40	55mm	40mm	45mm
Luna-s-55	70mm	55mm	50mm
Luna-s-70	85mm	70mm	65mm

