


MARELUCE
outdoor

delta-s



Technical Data	
Power	2W
Voltage Supply	3-45VDC (Driver Inc.)
Dimmable	Yes / PWM
Color Temp.	2700K-3000K-4000K
Luminous Flux	110lm/Watt (Max.)
Light Source	COB Led / CRI>90
Beam	45°
Body Material	SS 316L
Body Finishes	PSS-SSS-G-MBR-RAL
IP Class	66

Dimensions



Model	a	b
Delta-S	40mm	32mm

Options Controls




delta-m



Technical Data	
Power	5W
Voltage Supply	3-45VDC (Driver Inc.)
Dimmable	Yes / PWM
Color Temp.	2700K-3000K-4000K
Luminous Flux	110lm/Watt (Max.)
Light Source	COB Led / CRI>90
Beam	45°
Body Material	SS 316L
Body Finishes	PSS-SSS-G-MBR-RAL
IP Class	66

Dimensions



Model	a	b
Delta-M	60mm	45mm

Options Controls




delta-l



Technical Data	
Power	10W
Voltage Supply	3-45VDC (Driver Inc.)
Dimmable	Yes / PWM
Color Temp.	2700K-3000K-4000K
Luminous Flux	110lm/Watt (Max.)
Light Source	COB Led / CRI>90
Beam	45°
Body Material	SS 316L
Body Finishes	PSS-SSS-G-MBR-RAL
IP Class	66

Dimensions



Model	a	b
Delta-L	80mm	65mm

Options Controls




delta-xl



Technical Data	
Power	15W
Voltage Supply	3-45VDC (Driver Inc.)
Dimmable	Yes / PWM
Color Temp.	2700K-3000K-4000K
Luminous Flux	110lm/Watt (Max.)
Light Source	COB Led / CRI>90
Beam	45°
Body Material	SS 316L
Body Finishes	PSS-SSS-G-MBR-RAL
IP Class	66

Dimensions



Model	a	b
Delta-XL	90mm	75mm

Options Controls




atlantis



Technical Data	
Power	10W-20W (2 Model)
Voltage Supply	3-45VDC (Driver Ext.)
Dimmable	Yes / PWM
Color Temp.	2700K-3000K-4000K-6500K-RGB
Luminous Flux	110lm/Watt (Max.)
Light Source	COB Led / CRI>90
Beam	90°
Body Material	SS 316L
Body Finishes	PSS-SSS-G-MBR-RAL
IP Class	66

Dimensions



Model	a	b
Atlantis	93mm	90mm

Options Controls




atlas-s



Technical Data	
Power	3W-6W (2 Model)
Voltage Supply	8-32VDC (Driver Inc.)
Dimmable	Yes / PWM
Color Temp.	2700K-3000K-4000K-DW-RGB
Luminous Flux	125lm/Watt (Max.)
Light Source	High Power Led / CRI>80
Beam	Ultra Wide
Body Material	SS 316L
Body Finishes	PSS-SSS-G-MBR-RAL
IP Class	66

Dimensions



Model	a	b	c
Atlas-s	100mm	70mm	80mm

Options Controls




atlas-m



Technical Data	
Power	3W-6W (Model)
Voltage Supply	8-32VDC (Driver Inc.)
Dimmable	Yes / PWM
Color Temp.	2700K-3000K-4000K-DW-RGB
Luminous Flux	125lm/Watt (Max.)
Light Source	High Power Led / CRI>80
Beam	Ultra Wide
Body Material	SS 316L
Body Finishes	PSS-SSS-G-MBR-RAL
IP Class	66

Dimensions



Model	a	b	c
Atlas-m	100mm	70mm	120mm

Options Controls



fauna-v



Technical Data	
Power	6W
Voltage Supply	3-45VDC (Driver Ext.)
Dimmable	Yes / PWM
Color Temp.	2700K-3000K-4000K
Luminous Flux	110lm/Watt (Max.)
Light Source	COB Led / CRI>80
Beam	60°-110°
Body Material	SS 316L
Body Finishes	PSS-SSS-G-MBR-RAL
IP Class	66

Dimensions



Model	a	b
Fauna-v	60mm	35mm

Options Controls



fauna



Technical Data	
Power	6W
Voltage Supply	3-45VDC (Driver Ext.)
Dimmable	Yes / PWM
Color Temp.	2700K-3000K-4000K
Luminous Flux	110lm/Watt (Max.)
Light Source	COB Led / CRI>80
Beam	60°-110°
Body Material	SS 316L
Body Finishes	PSS-SSS-G-MBR-RAL
IP Class	66

Dimensions



Model	a	b
Fauna	50mm	35mm

Options Controls




leo-r



Technical Data	
Power	4W-8W-12W (3 Model)
Voltage Supply	3-45VDC (Driver Inc.)
Dimmable	Yes / PWM
Color Temp.	2700K-3000K-4000K-6500K
Luminous Flux	110lm/Watt (Max.)
Light Source	COB Led / CRI>90
Beam	36°
Body Material	SS 316L
Body Finishes	PSS-SSS-G-MBR-RAL
IP Class	66

Dimensions



Model	a	b	c
Leo-R-50	50mm	40mm	65mm
Leo-R-70	70mm	60mm	90mm
Leo-R-90	90mm	80mm	90mm

Options Controls




leo-s



Technical Data	
Power	4W-8W-12W (3 Model)
Voltage Supply	3-45VDC (Driver Inc.)
Dimmable	Yes / PWM
Color Temp.	2700K-3000K-4000K-6500K
Luminous Flux	110lm/Watt (Max.)
Light Source	COB Led / CRI>90
Beam	36°
Body Material	SS 316L
Body Finishes	PSS-SSS-G-MBR-RAL
IP Class	66

Dimensions



Model	a	b	c
Leo-S-50	50mm	40mm	65mm
Leo-S-70	70mm	60mm	90mm
Leo-S-90	90mm	80mm	90mm

Options Controls




nero



Technical Data	
Power	5W-10W (2 Model)
Voltage Supply	3-45VDC (Driver Inc.)
Dimmable	Yes / PWM
Color Temp.	2700K-3000K-4000K-6500K
Luminous Flux	110lm/Watt (Max.)
Light Source	COB Led / CRI>90
Beam	45°
Body Material	SS 316L
Body Finishes	PSS-SSS-G-MBR-RAL
IP Class	66

Dimensions



Model	a	b	c
Nero-50	65mm	50mm	45mm
Nero-60	85mm	70mm	55mm

Options Controls




boa



Technical Data	
Power	6W-12W (2 Model)
Voltage Supply	18-32VDC (Driver Inc.)
Dimmable	Yes / PWM
Color Temp.	2700K-3000K-4000K-6500K
Luminous Flux	125lm/Watt (Max.)
Light Source	High Power Led / CRI>80
Beam	60°
Body Material	SS 316L
Body Finishes	PSS-SSS-G-MBR-RAL
IP Class	66

Dimensions



Model	a	b	c
Nero-50	80mm	50mm	55mm
Nero-70	100mm	70mm	55mm

Options Controls

