


MARELUCE
reading light

polaris-s



Technical Data	
Power	2W
Voltage Supply	3-32VDC (Driver Inc.)
Dimmable	Yes / PWM
Color Temp.	2700K-3000K-4000K
Luminous Flux	125lm/Watt (Max.)
Light Source	High Power Led / CRI>80
Beam	45°
Body Material	SS 316L - Aluminum
Body Finishes	PSS-SSS-G-MBR-RAL
IP Class	44

Dimensions



Model	a	b	c
Polaris-S	32mm	300mm	80mm

Options Controls




polaris-f



Technical Data	
Power	2W
Voltage Supply	3-32VDC (Driver Inc.)
Dimmable	Yes / PWM
Color Temp.	2700K-3000K-4000K
Luminous Flux	125lm/Watt (Max.)
Light Source	High Power Led / CRI>80
Beam	45°
Body Material	SS 316L - Aluminum
Body Finishes	PSS-SSS-G-MBR-RAL
IP Class	44

Dimensions



Model	a	b	c
Polaris-F	32mm	300mm	80mm

Options Controls




victoria



Technical Data	
Power	2W
Voltage Supply	3-32VDC (Driver Inc.)
Dimmable	Yes / PWM
Color Temp.	2700K-3000K-4000K
Luminous Flux	125lm/Watt (Max.)
Light Source	High Power Led / CRI>80
Beam	45°
Body Material	SS 316L - Aluminum
Body Finishes	PSS-SSS-G-MBR-RAL
IP Class	44

Dimensions



Model	a	b	c
Victoria	60mm	40mm	110mm

Options Controls




tureis-s



Technical Data	
Power	2W
Voltage Supply	3-32VDC (Driver Inc.)
Dimmable	Yes / PWM
Color Temp.	2700K-3000K-4000K
Luminous Flux	125lm/Watt (Max.)
Light Source	High Power Led / CRI>80
Beam	45°
Body Material	SS 316L - Aluminum
Body Finishes	PSS-SSS-G-MBR-RAL
IP Class	44

Dimensions



Model	a	b	c
Tureis-S	32mm	300mm	120mm

Options Controls




tureis-f



Technical Data	
Power	2W
Voltage Supply	3-32VDC (Driver Inc.)
Dimmable	Yes / PWM
Color Temp.	2700K-3000K-4000K
Luminous Flux	125lm/Watt (Max.)
Light Source	High Power Led / CRI>80
Beam	45°
Body Material	SS 316L - Aluminum
Body Finishes	PSS-SSS-G-MBR-RAL
IP Class	44

Dimensions



Model	a	b	c
Tureis-F	32mm	300mm	120mm

Options Controls




diana



Technical Data	
Power	2W
Voltage Supply	3-32VDC (Driver Inc.)
Dimmable	Yes / PWM
Color Temp.	2700K-3000K-4000K
Luminous Flux	125lm/Watt (Max.)
Light Source	High Power Led / CRI>80
Beam	45°
Body Material	SS 316L - Aluminum
Body Finishes	PSS-SSS-G-MBR-RAL
IP Class	44

Dimensions



Model	a	b	c
Diana	55mm	70mm	170mm

Options Controls




vegis-m



Technical Data	
Power	2W
Voltage Supply	3-32VDC (Driver Inc.)
Dimmable	Yes / PWM
Color Temp.	2700K-3000K-4000K
Luminous Flux	125lm/Watt (Max.)
Light Source	High Power Led / CRI>80
Beam	45°
Body Material	SS 316L - Aluminum
Body Finishes	PSS-SSS-G-MBR-RAL
IP Class	44

Dimensions



Model	a	b	c
Vegis-M	30mm	300mm	60mm

Options Controls




vegis-s



Technical Data	
Power	2W
Voltage Supply	3-32VDC (Driver Inc.)
Dimmable	Yes / PWM
Color Temp.	2700K-3000K-4000K
Luminous Flux	125lm/Watt (Max.)
Light Source	High Power Led / CRI>80
Beam	45°
Body Material	SS 316L - Aluminum
Body Finishes	PSS-SSS-G-MBR-RAL
IP Class	44

Dimensions



Model	a	b
Vegis-S	30mm	60mm

Options Controls




iris-m



Technical Data	
Power	2W
Voltage Supply	3-32VDC (Driver Inc.)
Dimmable	Yes / PWM
Color Temp.	2700K-3000K-4000K
Luminous Flux	125lm/Watt (Max.)
Light Source	High Power Led / CRI>80
Beam	45°
Body Material	SS 316L - Aluminum
Body Finishes	PSS-SSS-G-MBR-RAL
IP Class	44

Dimensions



Model	a	b	c
Iris-M	28mm	70mm	28mm

Options Controls




iris-s



Technical Data

Power	2W
Voltage Supply	3-32VDC (Driver Inc.)
Dimmable	Yes / PWM
Color Temp.	2700K-3000K-4000K
Luminous Flux	125lm/Watt (Max.)
Light Source	High Power Led / CRI>80
Beam	45°
Body Material	SS 316L - Aluminum
Body Finishes	PSS-SSS-G-MBR-RAL
IP Class	44

Dimensions



Model	a	b	c
Iris-S	28mm	300mm	28mm

Options Controls


nemesis-m



Technical Data

Power	2W
Voltage Supply	3-32VDC (Driver Inc.)
Dimmable	Yes / PWM
Color Temp.	2700K-3000K-4000K
Luminous Flux	125lm/Watt (Max.)
Light Source	High Power Led / CRI>80
Beam	45°
Body Material	SS 316L - Aluminum
Body Finishes	PSS-SSS-G-MBR-RAL
IP Class	44

Dimensions



Model	a	b	c
Nemesis-M	28mm	70mm	28mm

Options Controls


nemesis-s



Technical Data

Power	2W
Voltage Supply	3-32VDC (Driver Inc.)
Dimmable	Yes / PWM
Color Temp.	2700K-3000K-4000K
Luminous Flux	125lm/Watt (Max.)
Light Source	High Power Led / CRI>80
Beam	45°
Body Material	SS 316L - Aluminum
Body Finishes	PSS-SSS-G-MBR-RAL
IP Class	44

Dimensions



Model	a	b	c
Nemesis-S	28mm	70mm	28mm

Options Controls