OUTDOOR COLLECTION

ATLANTIS

Outdoor COB luminaire in SS 316L · 10 / 20 W · 90° beam · IP66



POWER 10 · 20 W	EFFICACY 110 lm/W
LIGHT SOURCE COB · CRI 90	BEAM 90°
PROTECTION IP66	BODY SS 316L

Overview

ATLANTIS is an outdoor COB luminaire with a body in marine-grade SS 316L stainless steel. A COB LED source with CRI 90 delivers up to 110 lm/W with a 90° beam. It is available in 10 W / 20 W, comes in 2700K, 3000K, 4000K, 6500K or RGB and runs on 3–45 VDC from an external driver. It dims via PWM and can be integrated into 1–10V, DMX512, DALI and Wi-Fi control systems. With IP66 protection and ten body finishes, ATLANTIS is built for decks, exteriors and other exposed areas on board.

Specifications

Power	10 W / 20 W (2 models)
Supply voltage	3–45 VDC
Driver	External (not included)
Dimming	PWM
Colour temperature	2700K / 3000K / 4000K / 6500K / RGB
Luminous efficacy	110 lm/W (max.)
Light source	COB LED
Colour rendering	CRI 90
Beam	90°
Body material	SS 316L stainless steel
Body finishes	10 options (see page 2)
IP rating	IP66
Operating temperature	–30 °C … +50 °C
Protection class	III
Installation	Surface mounted

Front View



Compliance

UKCA
UK conformity assessed

CE
European conformity

RoHS
RoHS compliant

Class III
Safety extra-low voltage

F mark
For normally flammable surfaces

–30 °C … +50 °C
Operating temperature


ORDERING INFORMATION

Product Code

ATLANTIS	93	10 · 20	316	PSS ... G	2700K · 3000K · 4000K · 6500K · RGB
MODEL Outdoor	SIZE	POWER (W)	BODY SS 316L	FINISH See body finishes	CCT

Example: ATLANTIS-93-20-316-MSS-3000K — Atlantis, 20 W, SS 316L, matt 316L finish, 3000K

Dimensions (mm)



Models

MODEL	CODE	POWER	A	B	C
Atlantis	ATLANTIS-93-10	10 W	93	90	–
Atlantis	ATLANTIS-93-20	20 W	93	90	–

Dimensions as given in the catalogue. All dimensions in mm.

Body Finishes

- **PSS** Polished 316L
- **MSS** Matt 316L
- **SSS** Satine 316L
- **MB** Matt Black
- **MW** Matt White
- **RAL** RAL Code
- **AN** Silver Anodised
- **MBR** Matt Bronze
- **MG** Matt Gold
- **G** Gold


Beam



Colour Temperature

- 2700K Extra warm white
- 3000K Warm white
- 4000K Neutral white
- 6500K Cool white
- RGB RGB colour

Control Options



- **PWM** — integrated dimming
- **1–10V** — via compatible controller
- **DMX512** — via compatible decoder
- **DALI** — via compatible controller
- **Wi-Fi** — via compatible Wi-Fi controller

Light output and power may vary by up to ±10% due to production and component tolerances. Driver not included; select a driver matching the luminaire power and