MARINE
PREMIUM LED LIGHT

MARINELED · UNDERWATER LIGHTING

MARIS-9

Underwater light · 27 W single colour / RGB · 36 W RGBW · 90° beam · IP68



MARIS-9 · ANTHRACITE

POWER	LIGHT OUTPUT
27 / 36 W	3375 – 4500 lm
BEAM ANGLE	**PROTECTION**
90°	IP68
SUPPLY	**BODY**
10–30 VDC	Aluminium · SS 316L

OVERVIEW

MARIS-9 is a MarineLed underwater light for installation below the waterline. Its body is available in aluminium (anthracite, silver or bronze anodised) or SS 316L stainless steel with a polished chrome finish, and the optic is protected by a tempered-glass diffuser. Single-colour and RGB versions draw 27 W (3375 lm), the RGBW version 36 W (4500 lm), all with a 90° beam. MARIS-9 is offered in white, green, blue, red, RGB and RGBW, runs on 10–30 VDC from an external driver and can be controlled via Wi-Fi, DMX512, DALI or simple on/off switching. Rated IP68, it is made for continuous submersion.

SPECIFICATIONS

Power	**Single colour, RGB: 27 W · RGBW: 36 W**
Supply voltage	**10–30 VDC**
Driver	**External (not included)**
Light output	**27 W: 3375 lm · 36 W: 4500 lm**
Light colours	**White, green, blue, red, RGB, RGBW**
Beam angle	**90°**
Body material	**Aluminium / SS 316L**
Body finish	**Anthracite, silver, bronze anodised (aluminium) · polished chrome (SS 316L)**
Diffuser	**Tempered glass**
Dimensions	**Ø110 mm × 26 mm**
IP rating	**IP68**
Control	**Wi-Fi, DMX512, DALI, on/off**
Installation	**Below the waterline**

SIDE VIEW



MARIS-9 · Ø110 mm × 26 mm

VERSIONS

Single colour	**27 W**
RGB	**27 W**
RGBW	**36 W**

MARINE
PREMIUM LED LIGHT

ORDERING INFORMATION

PRODUCT CODE

MARIS-9	110	27 · 36	AL · 316	ANT · SIL · BAN · PCH	WH · GR · BL · RD · RGB · RGBW	1030	WIFI · DMX · DALI · ONOFF	90
MODEL	Ø MM	WATT	BODY	FINISH	COLOUR	VDC	CONTROL	BEAM

Example: **MARIS-9-110-36-AL-ANT-RGBW-1030-DMX-90** — MARIS-9, RGBW 36 W, aluminium, anthracite, DMX512 control, 90° beam

MODELS

MODEL	CODE	POWER	LIGHT OUTPUT	Ø	HEIGHT
MARIS-9	MARIS-9-110-27	27 W	3375 lm	110 mm	26 mm
MARIS-9 RGBW	MARIS-9-110-36	36 W	4500 lm	110 mm	26 mm

BODY FINISHES



ANT
Anthracite
Aluminium



SIL
Silver
Aluminium



BAN
Bronze anodised
Aluminium




PCH
Polished chrome
SS 316L

LIGHT COLOURS

- **White** — Single colour
- **Green** — Single colour
- **Blue** — Single colour
- **Red** — Single colour
- **RGB** — Colour changing
- **RGBW** — RGB + white

BEAM ANGLE



90° · wide beam

CONTROL OPTIONS

Wi-Fi
via app

DMX512
via DMX512 controller

DALI
via DALI controller

On / Off
switched supply

Light output and power may vary by up to ±10% due to production and component tolerances. Driver not included; select a driver matching the luminaire power and the 10–30 VDC supply range.