COURTESY LIGHT COLLECTION

NORA-S2L

Compact courtesy light in SS 316L or aluminium · 2 W · 15° – 110° beam



POWER 2 W	EFFICACY 125 lm/W
LIGHT SOURCE LED · CRI 80	BEAM 15° – 110°
PROTECTION IP44 – IP66	BODY SS 316L · Al


Overview

NORA-S2L is a compact courtesy light with a body in marine-grade SS 316L stainless steel or aluminium. A high-power LED source with CRI 80 delivers up to 125 lm/W with a 15° – 110° beam. It draws 2 W, comes in 2700K, 3000K or 4000K and runs on 3–32 VDC with an integrated driver. It dims via PWM and can be integrated into 1–10V, DMX512, DALI and Wi-Fi control systems. With IP44 to IP66 protection and ten body finishes, NORA-S2L suits steps, walkways and passageways on board.

Specifications

Power	2 W
Supply voltage	3–32 VDC
Driver	Integrated
Dimming	PWM
Colour temperature	2700K / 3000K / 4000K
Luminous efficacy	125 lm/W (max.)
Light source	High-power LED
Colour rendering	CRI 80
Beam	15° – 110°
Body material	SS 316L or aluminium
Body finishes	10 options (see page 2)
IP rating	IP44 – IP66
Operating temperature	–30 °C … +50 °C
Protection class	III
Installation	Recessed

Front View



Compliance

UKCA
UK conformity assessed

CE
European conformity

RoHS
RoHS compliant

Class III
Safety extra-low voltage

F mark
For normally flammable surfaces

–30 °C … +50 °C
Operating temperature


ORDERING INFORMATION

Product Code

NORA-S2L	2	316 · AL	PSS ... G	2700K · 3000K · 4000K
MODEL Courtesy Light	POWER (W)	BODY SS 316L / Aluminium	FINISH See body finishes	CCT

Example: NORA-S2L-2-316-MSS-3000K — Nora-S2L, 2 W, SS 316L, matt 316L finish, 3000K

Dimensions (mm)



Models

MODEL	CODE	POWER	A	B	C
Nora-S2L	NORA-S2L-2	2 W	40	28	27

All dimensions in mm.

Body Finishes

- **PSS** Polished 316L
- **MSS** Matt 316L
- **SSS** Satine 316L
- **MB** Matt Black
- **MW** Matt White
- **RAL** RAL Code
- **AN** Silver Anodised
- **MBR** Matt Bronze
- **MG** Matt Gold
- **G** Gold


Beam



Colour Temperature

- 2700K Extra warm white
- 3000K Warm white
- 4000K Neutral white

Control Options



- **PWM** — integrated dimming
- **1–10V** — via compatible controller
- **DMX512** — via compatible decoder
- **DALI** — via compatible controller
- **Wi-Fi** — via compatible Wi-Fi controller

Light output and power may vary by up to ±10% due to production and component tolerances. Driver integrated; supply 3–32 VDC. IES files available on request.